	Unit			Emissions			Emissions														
		Projected		reductions	Control strategy	Controlled	reductions									Total ozone					
Source		emissions (tons)	Allowances	needed (tons)		emissions (tons)	achieved (tons)	Control equipment cost				Monitoring cost				season cost			Cooto odivotod	for aminaian	. Ann allin m
			Anowarices	(10115)		(10115)	(toris)		Ozone	Julpment cost			Monito	ring cost		(control	1		Costs adjusted for emissions trading adjusted		
									season	Total ozone	Cost	Number of		Anuual	Annualized	equipment and	Overall cost			ozone	
										season cost	effectiveness	CEMS	Startup	monitoring	monitoring	monitoring) -	effectiveness	spare	income@2500/al		
								Capital cost (\$)			(\$/ton)	needed	cost (\$)	cost (\$)	cost (\$)	(\$)	(\$/ton)	allowances		(\$)	cost effectiveness(\$/ton)
									(*)	(-,	,		(,,	(,,	(,,	(0)	(\$7,1011)			,	,
National																					
Steel	Boiler	189	34		shut down																
												CEM in									
IPL-Perry-K	unit 11	252	115	137	switched to gas firing in 1999	45	207					place									
IPL-Perry-K		252			low Nox burner	126			52,770	405,849	3,221		1 180,000	37,517	66,677	472,526					
												CEM in									
IPL-Perry-K	unit 13	167	64	103	switched to gas firing in 1999	26	141					place									
												CEM in									
IPL-Perry-K	unit 14	167	59	108	switched to gas firing in 1999	27	140					place									
IPL-Perry-K		57				57						f -	1 180,000	37,517	66,677	66,677					
IPL-Perry-K		57				57							1 180,000			66,677					
	Totals	952				337		2,169,455	52,770	405,849			3 540,000			605,880	985	115	287,975	317,905	517
		1	1	1			1	,,		,			1	,	,	,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,		1	1,000	. ,	
		1			low NOX burner & staged							CEM in							1		
New Energy	Boiler	631	241	390		241	390	4,028,201	91.377	746,967	1.914	place				746.967	1.914		0	746,967	1.914
									- /-	-,						-,	, ,			-,	
												CEM in									
ALCOA	unit1	1,260	1,019	241	low Nox burner	630	630	4,874,964	229,650	1,023,050	1.623	place				1,023,050	1,623	3			
ALCOA	unit2	827	988	(161)		827				1,020,000	-,		+			.,,	.,				
ALCOA	unit3	1,215	959	256		1,215															
7120071	Totals	3,302	2,966	336		2,672	630		229,650	1,023,050	1,623					1,023,050	1,623	294	735,000	288,050	457
		-,,,,,	_,,,,,			-,		1,011,001		1,020,000	-,		+			.,,	.,		,		
	#3 Power																				
AMOCO	Station																				
	Boiler #1	433	287	146	low Nox burner	216	216	2,522,605	41.863	452,418	2.091		1 180,000	37,517	66,677	519.095					
	Boiler #2	433	287	146	low Nox burner	216			41,863	452,418	2,091		1 180,000			519,095					
	Boiler #3	433		146	low Nox burner	216			41,863		2.091		1 180,000	37,517		519.095					
	Boiler #4	433		146	low Nox burner	216			41.863		2.091		1 180,000	37,517		519,095					
	Boiler #5	433	287	146		433	s c	, , , , , , , , , , , , , , , , , , , ,	,				1 180,000			66,677					
	#1 Power						1						,	51,511							
	Station																				
	Boiler #1	9	24	(15)		24							1 180,000	37,517	66.677	66,677					
	Boiler #2	9				24							1 180,000			66,677			1		
l	Boiler #3	9				24				†			1 180,000			66,677		1	1		
	Boiler #4	9				24		l .					1 180,000			66,677			1		
	Boiler#5	9				24							1 180,000			66,677					
	Totals	2,210	1,555			1,418		10,090,420	167,452	1,809,671	2,091		1,800,000			2,476,441	2,862	210	525,250	1,951,191	2,255
	Overall																, , ,				
l	totals	7,096	5,214	1,882		4,668	2,501	21,163,040	541,249	3,985,537						4,852,338	1,940	619	1,548,225	3,304,113	1,321
		Total spare																			
		allowances	619							1									1		
										1								İ			
		Control equipment cost were estimated using USEPA's ACT document for Industrial/Institutional/Commercial boilers. Those																			
		costs are in 1992 dollars. The costs were adjusted to 1998 \$ using an estimated 1992/1998 inflation factor equal to 1.114.																			
		CEMs costs are in 1998 \$.The costs are not estimated for units with existing CEMS.																			
		3 A 50% cont	rol efficiency ba	s heen assum	ned for low NOX hurners Since	I NR is an v	ear-around o	ontrol actual coe													
		3. A 50% control efficiency has been assumed for low NOX burners. Since LNB is an year-around control, actual cost effectiveness ratio may be lower.																			
		Shutdown units are not included in the cost estimates.											1		1			1	1		
											1				1				·		1

1

12/27/00